

Libratus: The Superhuman AI for No-Limit Poker (Demonstration)

Noam Brown

Computer Science Department
Carnegie Mellon University

Tuomas Sandholm*

Computer Science Department
Carnegie Mellon University
and Strategic Machine, Inc.

Abstract

No-limit Texas Hold'em is the most popular variant of poker in the world. Heads-up no-limit Texas Hold'em is the main benchmark challenge for AI in imperfect-information games. We present *Libratus*, the first—and so far only—AI to defeat top human professionals in that game. *Libratus*'s architecture features three main modules, each of which has new algorithms: pre-computing a solution to an abstraction of the game which provides a high-level blueprint for the strategy of the AI, a new nested subgame-solving algorithm which repeatedly calculates a more detailed strategy as play progresses, and a self-improving module which augments the pre-computed blueprint over time.

1 Introduction

Recreational games have long been used in AI as benchmarks to evaluate the progress of the field. AIs have beaten top humans in chess [Campbell *et al.*, 2002] and Go [Silver *et al.*, 2016]. Checkers was even completely solved [Schaeffer *et al.*, 2007]. However, these are perfect-information games: both players know the exact state of the game at every point. In contrast, poker is an imperfect-information game: part of the state is hidden from a player because the other player has private information. Many real-world applications can be modeled as imperfect-information games, such as negotiations, business strategy, security interactions, and auctions. Indeed, imperfect information is common in the real world, while perfect information is rare, making imperfect-information games particularly suitable for modeling real-world strategic interactions. Dealing with hidden information requires drastically different AI techniques. Heads-up no-limit Texas Hold'em has long been the primary benchmark challenge for imperfect-information games.

In January 2017 *Libratus* beat a team of four top-10 heads-up no-limit specialist professionals in a 120,000-hand 20-day *Brains vs. AI* challenge match. That is the first time an AI has beaten top humans in this game. *Libratus* beat the humans by a large margin (147 mbb/hand), with 99.98% statistical significance. It also beat each of the humans individually.

2 Architecture of *Libratus*

Libratus's strategy was not programmed in, but rather generated algorithmically. The algorithms are domain-independent

and have applicability to a variety of imperfect-information games. *Libratus* features three main modules, and is powered by new algorithms in each of the three:

1. Computing approximate Nash equilibrium strategies before the event.
2. Subgame solving during play.
3. Improving *Libratus*'s own strategy to play even closer to equilibrium based on what holes the opponents have been able to identify and exploit.

The next three subsections discuss these, respectively.

2.1 Abstraction and Equilibrium Finding

It is infeasible to pre-compute a strategy for each of the 10^{161} different decision points in heads-up no-limit Texas hold'em.^{1,2} However, many situations are strategically similar and can be treated identically at only a small cost. For example, there is little difference between a bet of \$500 and a bet of \$501. Rather than come up with a unique strategy for both of those situations, it is standard to group them together and treat them identically, so that only one strategy is generated for them. There are two kinds of such abstraction: *action abstraction* and *card abstraction*.

In action abstraction, only a few of the nearly 20,000 possible actions available at any point in the game are included in the abstraction for both the agent and the opponent. If, during actual play, the opponent chooses an action that is not in the abstraction, then it is standard to map that action to a nearby action that is in the abstraction. The actions that we included in the abstraction were determined by analyzing the most common actions taken by prior top AIs in the *Annual Computer Poker Competition (ACPC)*. For the first few actions of the game, the actions to include in the abstraction (i.e., bet sizes) were determined by a parameter optimization algorithm which converged to a locally optimal set of bet sizes [Brown and Sandholm, 2014].

In card abstraction, similar poker hands are bucketed together and treated identically. *Libratus* does not use any card abstraction on the first (preflop) and second (flop) betting rounds. The last two betting rounds, which are exponentially larger, are more coarsely abstracted. The 55 million different

¹The standard version of the game has 10^{161} because both players have \$20,000 and are limited to dollar-increment bets.

²Heads-up *limit* Texas Hold'em, a significantly smaller game with 10^{13} decision points, was essentially solved in 2015 [Bowling *et al.*, 2015; Tammelin *et al.*, 2015].

*Corresponding author. Email: sandholm@cs.cmu.edu

hand possibilities on the third round are grouped into 2.5 million buckets, and the 2.4 billion different possibilities on the fourth round are grouped into 1.25 million buckets. The idea is that solving this abstraction gives a detailed strategy for the first two betting rounds and a blueprint for the remaining two betting rounds; the subgame solver, discussed in the next subsection, will then refine the blueprint into a detailed strategy. The card abstraction algorithm was similar to that used in *Baby Tartanian8* [Brown and Sandholm, 2016a] (the winner of the 2016 ACPC) and *Tartanian7* [Brown *et al.*, 2015] (the winner of the 2014 ACPC). The abstraction algorithm took the game size from 10^{161} decision points down to 10^{12} .

We solved the abstract game via a distributed version of an improvement over *Monte Carlo Counterfactual Regret Minimization* (MCCFR) [Zinkevich *et al.*, 2007; Lanctot *et al.*, 2009; Brown *et al.*, 2015]. MCCFR is an iterative algorithm which independently minimizes regret at every decision point. If both players play according to MCCFR in a two-player zero-sum game, then their average strategies provably converge to a Nash equilibrium. *Libratus* improves over vanilla MCCFR through a sampled form of *Regret-Based Pruning* (RBP) [Brown and Sandholm, 2015] (which we also used in our *Baby Tartanian8* agent [Brown and Sandholm, 2016a]). At a high level, our improvement is that paths in the tree that have very negative regret (for the player that is being updated on the current iteration) are visited less often. This leads to a significant speed improvement, thereby enabling a large fine-grained abstraction to be solved. It also mitigates the downsides of imperfect-recall abstraction (which is the state of the art) because the effective in-degree of abstract states decreases as some paths to them get de-emphasized.

2.2 Nested Safe Subgame Solving

The second module solves a finer-grained abstraction of the remaining game, taking into account the blueprint of the strategy for the entire game, when the third round is reached. Unlike perfect-information games, an imperfect-information subgame cannot be solved in isolation. The Nash equilibrium strategy in other subgames affects the optimal strategy in the subgame that is reached during play. Nevertheless, we can approximate a good strategy in the subgame that is reached if we have a good estimate of the *value* of reaching the subgame in an equilibrium. The first module estimated this value for every subgame. Using these subgame values as input, subgame solving creates and solves a finer-grained abstraction in the subgame that is reached.

This finer-grained abstraction does not use any card abstraction and uses a dense action abstraction.

Also, rather than apply action translation as was done on the first two rounds, and has been done in prior poker AIs, *Libratus* constructs and solves a new subgame every time an opponent chooses an action that is not in the finer-grained abstraction (in practice, it constructs a new subgame every time the opponent bets). This allows it to avoid the rounding error due to action translation and leads to dramatically lower exploitability [Brown and Sandholm, 2017b].

Another novel subgame solver aspect is that it guarantees that the solution is no worse than the precomputed equilibrium approximation, taking into account the magnitude of

opponent’s mistakes in the hand so far to enlarge the strategy polytope that can be safely optimized over. This begets better strategies [Brown and Sandholm, 2017b] than prior subgame-solving techniques [Ganzfried and Sandholm, 2015; Burch *et al.*, 2014; Jackson, 2014; Moravcik *et al.*, 2016].

A further novel aspect is that *Libratus* changes its action abstraction in each subgame. Thus the opponents must adapt to new bet sizes in each subgame.

2.3 Self-Improvement

As described in Section 2.1, *Libratus* uses a dense action abstraction on the first two betting rounds. If an opponent does not bet an amount that is in the abstraction, the bet is rounded to a nearby size that is in the abstraction. This causes the AI’s strategy and estimates of the values of reaching subgames, to be slightly off. To improve upon this, in the background, the AI determined a small number of actions to add to the abstraction that would reduce this rounding error as much as possible. The choice of actions was based on a combination of which actions the opponents were choosing most frequently and how far those actions were from their nearest actions in the abstraction. Once an action was selected, a strategy was calculated for it in a similar manner to subgame solving, described in Section 2.2. From that point on, if that action (or a nearby one) were chosen by an opponent, then the newly solved subgame strategy would be used.

3 Agent Construction

In total, *Libratus* used about 25 million core hours. Of those, about 13 million core hours were used for exploratory experiments and evaluation. About 6 million core hours were spent on the initial abstraction and equilibrium finding component, another 3 million were used for nested subgame solving, and about 3 million were used on the self-improvement algorithm.

The equilibrium finding and self-improvement algorithms used 196 nodes on the Bridges supercomputer at the Pittsburgh Supercomputing Center. Each node has 128 GB of memory and 28 cores, but only 14 cores are used by the agent. An asymmetric abstraction was used that had more actions for the opponent, to better reduce the error resulting from action translation [Bard *et al.*, 2014].

The subgame solver used 50 nodes per game. Here we used CFR+ [Tammelin *et al.*, 2015] combined with specialized optimizations [Johanson *et al.*, 2011] for equilibrium finding. Recent work suggests that subgame solving could be even faster by leveraging warm starting [Brown and Sandholm, 2016b], new pruning techniques [Brown and Sandholm, 2017a], or first-order methods [Nesterov, 2005; Kroer *et al.*, 2017].

Acknowledgments

The research was supported by NSF grant 1617590, ARO award W911NF-17-1-0082, and XSEDE computing resources by the Pittsburgh Supercomputing Center. The *Brains vs. AI* match was sponsored by CMU, Rivers Casino, GreatPoint Ventures, Avenue4Analytics, TNG Technology Consulting, Artificial Intelligence, Intel, and Optimized Markets. Ben Clayman computed statistics of the play of our AIs.

References

- [Bard *et al.*, 2014] Nolan Bard, Michael Johanson, and Michael Bowling. Asymmetric abstractions for adversarial settings. In *International Conference on Autonomous Agents and Multi-Agent Systems (AAMAS)*, pages 501–508, 2014.
- [Bowling *et al.*, 2015] Michael Bowling, Neil Burch, Michael Johanson, and Oskari Tammelin. Heads-up limit hold'em poker is solved. *Science*, 347(6218):145–149, January 2015.
- [Brown and Sandholm, 2014] Noam Brown and Tuomas Sandholm. Regret transfer and parameter optimization. In *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence*, pages 594–601. AAAI Press, 2014.
- [Brown and Sandholm, 2015] Noam Brown and Tuomas Sandholm. Regret-based pruning in extensive-form games. In *Advances in Neural Information Processing Systems*, pages 1972–1980, 2015.
- [Brown and Sandholm, 2016a] Noam Brown and Tuomas Sandholm. Baby Tartanian8: Winning agent from the 2016 annual computer poker competition. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence (IJCAI-16)*, pages 4238–4239, 2016.
- [Brown and Sandholm, 2016b] Noam Brown and Tuomas Sandholm. Strategy-based warm starting for regret minimization in games. In *AAAI Conference on Artificial Intelligence (AAAI)*, 2016.
- [Brown and Sandholm, 2017a] Noam Brown and Tuomas Sandholm. Reduced space and faster convergence in imperfect-information games via pruning. In *International Conference on Machine Learning*, 2017.
- [Brown and Sandholm, 2017b] Noam Brown and Tuomas Sandholm. Safe and nested endgame solving for imperfect-information games. In *AAAI-17 Workshop on Computer Poker and Imperfect Information Games*, 2017.
- [Brown *et al.*, 2015] Noam Brown, Sam Ganzfried, and Tuomas Sandholm. Hierarchical abstraction, distributed equilibrium computation, and post-processing, with application to a champion no-limit texas hold'em agent. In *Proceedings of the 2015 International Conference on Autonomous Agents and Multiagent Systems*, pages 7–15. International Foundation for Autonomous Agents and Multiagent Systems, 2015.
- [Burch *et al.*, 2014] Neil Burch, Michael Johanson, and Michael Bowling. Solving imperfect information games using decomposition. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 602–608, 2014.
- [Campbell *et al.*, 2002] Murray Campbell, A Joseph Hoane, and Feng-Hsiung Hsu. Deep Blue. *Artificial intelligence*, 134(1-2):57–83, 2002.
- [Ganzfried and Sandholm, 2015] Sam Ganzfried and Tuomas Sandholm. Endgame solving in large imperfect-information games. In *International Conference on Autonomous Agents and Multi-Agent Systems (AAMAS)*, pages 37–45, 2015.
- [Jackson, 2014] Eric Jackson. A time and space efficient algorithm for approximately solving large imperfect information games. In *AAAI Workshop on Computer Poker and Imperfect Information*, 2014.
- [Johanson *et al.*, 2011] Michael Johanson, Kevin Waugh, Michael Bowling, and Martin Zinkevich. Accelerating best response calculation in large extensive games. In *Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI)*, pages 258–265, 2011.
- [Kroer *et al.*, 2017] Christian Kroer, Kevin Waugh, Fatma Kılınc-Karzan, and Tuomas Sandholm. Theoretical and practical advances on smoothing for extensive-form games. In *Proceedings of the ACM Conference on Economics and Computation (EC)*, 2017.
- [Lanctot *et al.*, 2009] Marc Lanctot, Kevin Waugh, Martin Zinkevich, and Michael Bowling. Monte Carlo sampling for regret minimization in extensive games. In *Proceedings of the Annual Conference on Neural Information Processing Systems (NIPS)*, pages 1078–1086, 2009.
- [Moravcik *et al.*, 2016] Matej Moravcik, Martin Schmid, Karel Ha, Milan Hladik, and Stephen Gaukrodger. Refining subgames in large imperfect information games. In *AAAI Conference on Artificial Intelligence (AAAI)*, 2016.
- [Nesterov, 2005] Yurii Nesterov. Excessive gap technique in nonsmooth convex minimization. *SIAM Journal of Optimization*, 16(1):235–249, 2005.
- [Schaeffer *et al.*, 2007] Jonathan Schaeffer, Neil Burch, Yngvi Björnsson, Akihiro Kishimoto, Martin Müller, Robert Lake, Paul Lu, and Steve Sutphen. Checkers is solved. *Science*, 317(5844):1518–1522, 2007.
- [Silver *et al.*, 2016] David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.
- [Tammelin *et al.*, 2015] Oskari Tammelin, Neil Burch, Michael Johanson, and Michael Bowling. Solving heads-up limit texas hold'em. In *Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI)*, pages 645–652, 2015.
- [Zinkevich *et al.*, 2007] Martin Zinkevich, Michael Johanson, Michael H Bowling, and Carmelo Piccione. Regret minimization in games with incomplete information. In *Proceedings of the Annual Conference on Neural Information Processing Systems (NIPS)*, pages 1729–1736, 2007.