

Charging Station Placement for Anonymous Mobile Agents: A Parameterized Complexity Perspective

Arun Kumar Das¹, Tesshu Hanaka², Nikolaos Melissinos³, Hirotaka Ono⁴

¹School of Computer and Information Sciences, University of Hyderabad, Hyderabad, India

²Kyushu University, Fukuoka, Japan

³CSI, Faculty of Mathematics and Physics, Charles University, Prague, Czech Republic

⁴Nagoya University, Nagoya, Japan

arunkumardas@uohyd.ac.in, hanaka@inf.kyushu-u.ac.jp, melissinos@iuuk.mff.cuni.cz,
ono@nagoya-u.jp

Abstract

We study the problem of optimally placing charging stations for a set of k anonymous mobile agents, each of which must reach a distinct terminal. The agents are identical and can travel only up to a given distance r on a single charge. The objective is to find a placement of charging stations so that every terminal can be assigned a unique agent capable of reaching it, and the number of charging stations is minimized. The problem is known to be NP-hard in general and solvable in polynomial time only on paths and cycles.

In this work, we comprehensively investigate the classical and parameterized complexity of the problem. We first design a polynomial-time algorithm that, given a set of candidate charging stations, decides whether a feasible assignment of agents to terminals exists. This result also establishes the membership of the problem in NP, which was not previously known. We then analyze the parameterized complexity of the problem. Our results show that the problem remains hard even when we consider different combinations of natural parameters and structural parameters of the given network, such as the distance r plus the tree-depth, or the number of charging stations plus feedback vertex set number. On the positive side, we present three fixed-parameter tractable (FPT) algorithms: one parameterized by the number of agents k , a second by modular-width, and a third by vertex cover number. Finally, we give a polynomial-time k -approximation algorithm, as well as a polynomial-time algorithm for trees, by solving a generalized version of the problem that allows for some charging stations to be pre-placed.

1 Introduction

Coordinating multiple agents in a shared working environment via routing and path planning has become a central problem in optimization and robotics [Wurman *et al.*, 2008]. The agents are typically autonomous mobile robots tasked

with performing specific operations within designated domains such as warehouses, hospitals, libraries, restaurants, military installations, and transportation systems. In practical settings, these agents are often identical with respect to key attributes, including speed, battery capacity, and computational capability. Depending on the nature of their tasks and the operational costs incurred by system operators, a variety of models have been proposed, with the most well-known being the VEHICLE ROUTING PROBLEM (VRP) and the MULTI-AGENT PATHFINDING (MAPF) problem. Naturally, many of these problems are computationally intractable. In particular, MAPF is known to be notoriously hard when multiple agents are required to reach agent-specific goals without collisions. Indeed, it remains NP-hard even on structurally simple networks, such as trees with a small number of internal vertices [Fioravantes *et al.*, 2025a].

In most cases, the agents operate under limited energy capacities and must periodically recharge their batteries to sustain continuous operation [Kundu and Saha, 2018; Kundu and Saha, 2021]. In practical environments such as warehouses, hospitals, road networks [Zhang *et al.*, 2022], and airborne delivery systems, the efficient placement of charging stations is crucial for ensuring cost-effective and reliable operations. Recent studies [Falchetta and Noussan, 2021] show a significant gap in the placement of charging infrastructure that leaves agents stranded due to depleted batteries. Nowadays, in the US [David Shepardson, 2025] and the EU [European Automobile Manufacturers’ Association, 2024], the problem of green energy adoption has become crucial, and consequently, both the placement of charging stations and the scheduling of recharging cycles have a significant impact on overall system performance by substantially reducing idle time and improving operational efficiency [Zhu *et al.*, 2025; Xiong *et al.*, 2015].

1.1 Our Model

In this work, we are interested in scenarios where we have multiple identical agents placed in a network together with a set of terminal positions. The movement of the agents is energy-dependent, and each agent requires recharging at least once every specific number of steps. The goal is to identify the minimum number of charging stations and their placement in the network such that each terminal is reachable by

a unique agent. We call this problem CHARGING STATION PLACEMENT.

In order to give a formal definition we need some graph-theoretical notation. Let $G = (V, E)$ be an undirected graph where $|V| = n$, C be a subset of V and r be a positive integer. A sequence of vertices $v_1, \dots, v_\ell$, $\ell \in \mathbb{N}$, where $v_i v_{i+1} \in E$, for all $i \in [\ell - 1]$, is called a walk between v_1 and v_ℓ . A walk W connecting s and t is a (C, r) -walk if it can be decomposed into a set of sub-walks $P_1, P_2, \dots, P_m$ such that:

1. for every $1 \leq i < m$, the last vertex of P_i is the first vertex of P_{i+1} ,
2. for every $1 \leq i < m$, the shared vertex of P_i and P_{i+1} belongs to C , and
3. the length of each sub-walk P_i , $i \in [m]$ is at most r .

In CHARGING STATION PLACEMENT, we are given an undirected graph $G = (V, E)$ with $|V| = n$ along with two sets of vertices S and T with $|S| = |T| = k$, together with a capacity r . We need to compute a minimum cardinality subset C of charging stations such that each target position in T can be occupied with exactly one robot using the chargers in C . We call C a *charger placement*, or simply, *placement*. Further, we say that a charger placement C is *feasible* if there exists a bijection $f : S \rightarrow T$ and for any pair $s, f(s)$ there exists (C, r) -walk in G that connects s and $f(s)$. Then CHARGING STATION PLACEMENT is formally defined as follows.

CHARGING STATION PLACEMENT

Input: Graph $G = (V, E)$, two sets of vertices $S \subseteq V$ and $T \subseteq V$, where $|S| = |T| = k$, and two positive integers r and c .

Question: Is there a feasible charger placement $C \subseteq V$ of size at most c in G ?

We denote by (G, S, T, r, c) an instance of CHARGING STATION PLACEMENT. Any feasible charger placement C of minimum size is called a *minimum charger placement*.

CHARGING STATION PLACEMENT has applications in scenarios where we have identical energy-dependent robots that need to reach specific places to perform some tasks. Other scenarios may assume fully electrical communities where everyone moves with electric vehicles, and some companies try to provide charging stations in order to allow their employees to reach their workplaces. In such scenarios, it is not unnatural to assume that the employees have received the same training and thus can be considered identical.

1.2 Our Assumptions and Limitations

The primary motivation behind our model is to minimize the number of charging stations. This is a rational objective, since in many cases, deploying additional charging stations is the primary challenge. This challenge may arise from various factors, such as budgetary constraints or regulations imposed by third parties. Therefore, our model is tailored with this obstacle in mind.

Motivated by this, we adopted the following assumptions. First, we do not consider the travel distance, focusing solely on reachability. Second, we consider the anonymous version

of the problem, i.e., the final agent–terminal matching is not restricted. We do not consider any timing limitations; i.e., we do not consider charging times or any restrictions imposed by the positions of the agents in the network.

Notably, these are some of the most common restrictions appearing in many path-finding problems. However, as previously noted, the current model is highly applicable even without incorporating any of these constraints.

1.3 Our Contribution

We provide a detailed study of the computational complexity of CHARGING STATION PLACEMENT, with an emphasis on its parameterized complexity. Table 1 summarizes our results. In section 3, we prove that the problem belongs to the class NP. To this end, we present a polynomial-time algorithm that, given a subset C , verifies whether it is a feasible solution of CHARGING STATION PLACEMENT.

In Section 4, we provide several hardness results, including NP-hardness on planar bipartite graphs of maximum degree 3, W[2]-hardness when parameterized by the number of chargers c , W[1]-hardness when parameterized by the feedback vertex set number fvs together with the number of charging stations c , and W[1]-hardness when parameterized by distance to stars dts of G or distance to clusters dtc , even for instances with $r = 1$. For the inapproximability, the problem admits no $(1 - \epsilon) \ln k$ -approximation algorithm even on split or bipartite graphs unless $P=NP$.

We then turn to algorithmic results. In Section 5, we present three FPT algorithms: one parameterized by the number of agents, a second by modular-width, and a third by vertex cover number. The first is obtained via a reduction to the well-studied STEINER TREE problem, while the second and third exploit structural properties of graphs with bounded modular-width and vertex cover number, respectively. Finally, we provide a polynomial-time algorithm for trees, as well as a polynomial-time k -approximation algorithm.

Due to space limitations, we omit several proofs or provide only proof sketches.

1.4 Related Work

Robot motion planning [Cesati and Wareham, 1995] is central to artificial intelligence and multi-agent systems, with a vast body of literature on path planning for mobile agents [Guo *et al.*, 2023]. Prior works address diverse optimization objectives, including minimizing total traveled distance [Liu *et al.*, 2019], ensuring collision avoidance [Fioravantes *et al.*, 2025b], and obstacle removal [Erickson and LaValle, 2013]. However, accommodating agents with limited energy introduces fundamentally different constraints, necessitating a distinct algorithmic perspective.

CHARGING STATION PLACEMENT is first introduced in [Das, 2025], proving it NP-hard in general networks and polynomial-time solvable on simple paths or cycles. To our knowledge, CHARGING STATION PLACEMENT is not studied elsewhere. However, since charging station placement is a central challenge in electric vehicle (EV) E-mobility, Storandt and Funke [Storandt and Funke, 2013] address related problems. They study the hardness of minimizing

Category	Parameter / Graph Class	Specific Constraint	Result	Ref.
Classical Complexity	Planar bipartite graphs ($\Delta = 6$)	$r = 1$	NP-complete	Thm. 2
	Planar bipartite graphs ($\Delta = 3$)	$r = 3$	NP-complete	Thm. 2
	Bipartite graphs ($\Delta = 4$)	$r = 1$	NP-complete	Thm. 2
	Trees		P	Thm. 9
Natural Parameters	Number of agents (k)	General graphs	FPT ($k^{O(k)}$)	Thm. 6
	Number of chargers (c)	Split graphs, $r = 1$	W[2]-hard	Thm. 3
	Number of chargers (c)	Bipartite graphs, $r = 1$	W[2]-hard	Thm. 2
	Number of chargers (c)	General graphs	XP ($n^{O(c)}$)	Cor. 2
Structural Parameters	Distance to clusters (dte)	Param. by dte + r	W[1]-hard	Thm. 4
	Distance to stars (dts)	Param. by dts + r	W[1]-hard	Thm. 4
	Feedback vertex set (fvs)	Param. by fvs + c	W[1]-hard [†]	Thm. 5
	Modular-width (mw)		FPT (2^{mw})	Thm. 7
	Vertex cover (vc)		FPT ($2^{2\text{vc}^2 + \text{vc}}$)	Thm. 8
Approximation	General graphs		k -Approx.	Thm. 10
	Split/Bipartite graphs		no $(1 - \epsilon) \ln k$ -approx.	Cor. 3

[†] No algorithm runs in time $n^{o(\text{fvs}+c)}$ assuming the ETH.

Table 1: Overview of the results for CHARGING STATION PLACEMENT.

charging stations in a directed graph where each pair of vertices needs to be reachable subject to recharge constraints. Strimel and Veloso [Strimel and Veloso, 2014] study finding a location minimizing charging stations when a single agent needs to reach a given set of targets following a predetermined path. Kundu and Saha introduce an INDOOR CHARGING STATION PLACEMENT problem: given a workspace graph and battery threshold, place the minimum number of stations so that any robot from any starting point can reach a station before running out of power [Kundu and Saha, 2018]. They formulate two variants (minimize stations given threshold, or find maximum threshold given station count), develop SMT-based algorithms, and later prove both variants NP-hard with polynomial-time approximation algorithms [Kundu and Saha, 2023; Kundu and Saha, 2021]. Kumar et al. formulate the persistent robot charging problem, which optimizes recharging schedules to minimize station utilization during extended missions [Kumar et al., 2025].

While identical agents often simplify models, this is not always the case. MAPF is one example where, considering identical agents (i.e., goals are not agent-specific), we can efficiently compute coalition-free schedules [Yu and LaValle, 2012]. However, the VRP, seeking optimal routes for a fleet of vehicles, is originally introduced as a “truck dispatching” problem for a homogeneous fleet [Dantzig and Ramser, 1959], yet remains computationally hard.

Our problem diverges significantly from both VRP and MAPF. Unlike VRP and MAPF, CHARGING STATION PLACEMENT minimizes charging stations rather than primarily bounding travel time. This aspect distinguishes our work from previous routing problems. Notably, beyond [Das, 2025], other works consider similar settings. Agarwal et al. [Agarwal et al., 2016] define a SHORTEST-PATH HITTING SET problem to place minimum charging stations so that every shortest path remains “EV-feasible” (traversable on

a full charge). A key distinction lies in our focus on traveling between specific starting and terminal positions, while SHORTEST-PATH HITTING SET guarantees feasibility between *any* pair via a shortest path. In some sense, our setting generalizes their model. Furthermore, we note that in practice, connecting all possible pairs is often unnecessary.

2 Preliminaries

Throughout this paper, we use standard graph theory notation and terminology. Let $G = (V(G), E(G))$ be an undirected graph with $|V(G)| = n$ vertices and $|E(G)| = m$ edges. When the context is clear, we omit the argument G (e.g., writing V and E). A directed arc from u to v is denoted by $\overrightarrow{uv}$, and an undirected edge between u and v is denoted by uv . We denote the distance between u and v by $\text{dist}(u, v)$.

For a vertex $v \in V$, the neighborhood of v is denoted by $N(v) = \{u \in V \mid uv \in E\}$. The degree of v is denoted by $\deg(v) = |N(v)|$. The maximum degree of G is denoted by $\Delta(G) = \max_{v \in V} \deg(v)$. For a positive integer r , the r -neighborhood of v is denoted by $N_r(v) = \{u \in V \mid \text{dist}(u, v) \leq r\}$. For a graph $G = (V, E)$, the r -th power of G , denoted by $G^r = (V, E^r)$, is a graph with vertex set V where $uv \in E^r$ if and only if the distance between u and v in G is at most r . Note that $G^1 = G$.

2.1 Natural and Structural Parameters

One of the main goals of this work is to study the parameterized complexity of CHARGING STATION PLACEMENT. In the parameterized complexity framework, in addition to an input instance, one is given a parameter x , and the objective is to design algorithms whose running time is efficient when x is small. A problem is *fixed-parameter tractable* (FPT) if there exists an algorithm that runs in time $f(x) \cdot n^{O(1)}$, where f is a computable function depending only on x , and n is the input size. Such an algorithm is called an *FPT algorithm*.

Some problems are believed not to admit FPT algorithms under standard complexity assumptions; such problems are called W[1]-hard.

We consider both *natural* parameters, such as the number c of charging stations or the number k of agents, and *structural* parameters of the underlying graph. The structural parameters used in this paper are the following:

- *Feedback vertex set number*, fvs: the size of a smallest set S such that $G - S$ is a forest.
- *Distance to stars*, dts: the size of a smallest set S such that $G - S$ is a disjoint union of stars.
- *Distance to clusters*, dtc: the size of a smallest set S such that $G - S$ is a disjoint union of cliques.

We also consider the *modular-width* mw of a graph. While the formal definition is rather technical, intuitively mw measures how well the vertex set can be recursively partitioned into *modules* where vertices of the same module have identical neighbors outside of the module. Finally, the set S of vertices is called a *vertex cover* if $u \in S$ or $v \in S$ for every edge $uv \in E$. The *vertex cover number* vc of G is defined by the size of a minimum vertex cover.

We note that these parameters are closely related to treewidth tw and cliquewidth cw . In particular, for any graph G , the inequalities $mw \leq 2^{vc} + vc$, $cw \leq dtc \leq vc$, and $tw - 1 \leq fvs \leq dts \leq vc$ hold. Consequently, the hardness results for fvs, dtc, and dts imply corresponding hardness results for tw and cw . Conversely, the FPT result for mw implies FPT results for other parameters, e.g., the vertex cover vc .

2.2 General Observations

Throughout this paper, we assume that the input graph is connected, as the global solution can be computed by solving the problem for each connected component of the input graph.

Then, we give several useful observations for CHARGING STATION PLACEMENT.

Observation 1. Let $G = (V, E)$ be a graph, $C \subseteq V$ and r a positive integer. Additionally, let (s_i, t_i) , $i \in [k]$ be k pairs of vertices. If $s_{i+1} = t_i \in C$ for all $i \in [k-1]$ and there exists a path P_i of length at most r between s_i and t_i , for all $i \in [k]$, then there exists a (C, r) -walk between s_1 and t_k .

Observation 2. Let $G = (V, E)$ be a graph, $C \subseteq V$ and r a positive integer. Additionally, let $W_{s,v}$ and $W_{t,v}$ be two (C, r) -walks between s and v , and between t and v respectively. If $v \in C$, then we can combine the two walks into a (C, r) -walk between s and t .

Proposition 1. An instance (G, S, T, r, c) of CHARGING STATION PLACEMENT is a yes-instance if and only if the instance $(G^r, S, T, 1, c)$ is a yes-instance.

3 NP-Membership

Let (G, S, T, r, c) be an instance of CHARGING STATION PLACEMENT and let $C \subseteq V(G)$ be a vertex set of order at most c . We prove that one can decide if C is a feasible solution of (G, S, T, r, c) in polynomial time. This implies that CHARGING STATION PLACEMENT belongs to the class NP.

We construct an intermediate directed graph D from G in the following way. The vertex set of D is $S \cup T \cup C$. Now, we construct the set of arcs in $A(D)$ as follows. For any vertex $u \in S \cup C$ we add the arcs $\vec{uv}$ in $A(D)$ if and only if $v \in N_r(u) \cap (T \cup C)$. Now, the following lemma is true for D .

Lemma 1. For any pair $(s, t) \in S \times T$, there exists a (C, r) -walk in G if and only if there exists a directed s - t path in D .

Then we consider an auxiliary bipartite graph H that is constructed as follows: For each vertex $s \in S$, we create a vertex u_s in H . For every vertex $t \in T$ we create a vertex v_t in H . Note that if a vertex w is both a starting and a terminal vertex, i.e., $w \in S \cap T$, then we create two vertices related to w : u_w representing that it is a starting vertex and v_w representing that it is a terminal vertex. We construct both vertices because we may have optimal solutions that do not match s with t , even if $s = t$. Then we introduce an edge between two vertices u_s and v_t in H if and only if there exists a directed path from s to t in D . We conclude the following lemma.

Lemma 2. The set C with $|C| \leq c$ is a feasible solution of (G, S, T, r, c) if and only if there exists a perfect matching in H .

Observe that the construction of both D and H can be performed in polynomial time. Indeed, the edges in $A(D)$ depend on $N_r(v)$ of v , which can be computed by a Breadth-First Search (BFS), and the edges of H can be computed using an algorithm for s - t paths in D . Both BFS and s - t paths can be computed in polynomial time [Cormen *et al.*, 2009]. Finally, computing a maximum matching can be done in polynomial time [Cormen *et al.*, 2009].

Theorem 1. Given an instance $\mathcal{I} = (G, S, T, r, c)$ and a set $C \subseteq V(G)$, we can decide in polynomial time whether C is a feasible solution of $\mathcal{I}$. Additionally, we can return a bijection $f : S \rightarrow T$ and a set of (C, r) -walks between s and $f(s)$ for $s \in S$.

Corollary 1. CHARGING STATION PLACEMENT belongs to NP.

We conclude by observing that given the number of chargers c , there are at most $n^{O(c)}$ possible placements of charging stations in any graph of order n . Therefore, by enumerating all potential solutions and checking their feasibility, we have the following corollary.

Corollary 2. CHARGING STATION PLACEMENT can be solved in time $n^{O(c)}$.

4 Hardness Results

We start by establishing NP-hardness even for instances where both r and $\Delta(G)$ are constants and G is bipartite.

Theorem 2. CHARGING STATION PLACEMENT is NP-hard even when:

- $r = 1$ and G is a planar bipartite graph with $\Delta(G) = 6$,
- $r = 1$ and G is a bipartite graph with $\Delta(G) = 4$,
- $r = 3$ and G is a planar bipartite graph with $\Delta(G) = 3$.

The proofs of all the statements appearing in Theorem 2 are based on reductions from VERTEX COVER.

In the following theorems, we show the parameterized hardness of CHARGING STATION PLACEMENT even on restricted graph classes. To do so, we give a parameterized reduction from SET COVER: Given a universe $U = \{u_1, \dots, u_n\}$, a family $\mathcal{F} = \{F_1, \dots, F_m\}$ of subsets of U , and an integer ℓ , the problem asks whether there exists a subfamily $\mathcal{F}' \subseteq \mathcal{F}$ such that $\bigcup_{F \in \mathcal{F}'} F = U$ and $|\mathcal{F}'| \leq \ell$. SET COVER is a well-known NP-complete problem [Garey and Johnson, 1979] and is W[2]-hard when parameterized by the solution size [Cygan *et al.*, 2015].

Theorem 3. CHARGING STATION PLACEMENT is W[2]-hard when parameterized by the number of charging stations c , even when $r = 1$ and the input graph is split or bipartite.

Proof sketch. We reduce from SET COVER, which is W[2]-hard parameterized by the solution size [Downey and Fellows, 1999]. Given $(U, \mathcal{F}, \ell)$, where $U = \{u_1, \dots, u_n\}$ and $\mathcal{F} = \{F_1, \dots, F_m\}$, we construct a split graph G as follows. Create a clique W with vertex set $\{w_F \mid F \in \mathcal{F}\}$ and, for each $u \in U$, two independent vertices s_u, t_u . Add edges $w_F s_u$ if $u \in F$, and $w_F t_u$ for all $(F, u) \in \mathcal{F} \times U$. Set $S = \{s_u \mid u \in U\}$, $T = \{t_u \mid u \in U\}$, $r = 1$, and $c = \ell$.

Finally, we can observe that a subfamily $\mathcal{F}' \subseteq \mathcal{F}$ with $|\mathcal{F}'| \leq \ell$ covers U if and only if $C = \{w_F \mid F \in \mathcal{F}'\}$ is a feasible charger placement with $|C| \leq \ell$: for each $u \in U$, the path s_u, w_F, t_u gives a $(C, 1)$ -walk whenever $u \in F$. Thus, this parameterized reduction shows the W[2]-hardness parameterized by c even when $r = 1$ and the input graph is split.

Observe that this reduction works even if we delete edges within W and the resulting graph is a bipartite graph. Therefore, the W[2]-hardness on bipartite graphs can also be shown by a similar argument. $\square$

Observe that our reduction in Theorem 3 preserves the objective value exactly. It is known that SET COVER cannot be approximated within $(1 - \epsilon) \ln |U|$ unless $P=NP$ [Dinur and Steurer, 2014]. As $|U| = |S| = |T| = k$, the following corollary holds.

Corollary 3. Unless $P=NP$, CHARGING STATION PLACEMENT cannot be approximated within $(1 - \epsilon) \ln k$ for any $\epsilon > 0$, even on split or bipartite graphs.

The next theorems consider structural parameters of the graph G . In particular, we consider the distance to clusters (d_{tc}) and the distance to stars (d_{ts}) as parameters.

Theorem 4. CHARGING STATION PLACEMENT is W[1]-hard when parameterized by distance to stars d_{ts} or distance to clusters d_{tc}, even when $r = 1$.

Proof sketch. We give a parameterized reduction from UNARY BIN PACKING. Given a multiset $\mathcal{E} = \{e_1, \dots, e_n\}$ of integers in unary and an integer $m \in \mathbb{N}$, the problem asks whether there is a partition of $\mathcal{E}$ into multisets $\mathcal{E}_1, \dots, \mathcal{E}_m$, such that, for all $j \in [m]$, $\sum_{e \in \mathcal{E}_j} e = (\sum_{e \in \mathcal{E}} e)/m$. It is known that UNARY BIN PACKING is W[1]-hard when parameterized by the number of bins m [Jansen *et al.*, 2013].

We start with an instance $(\mathcal{E}, m)$ of UNARY BIN PACKING. Let $B = (\sum_{e \in \mathcal{E}} e)/m$. We define a graph G together with the sets S and T as follows. First, we create m vertices $v_1, \dots, v_m$. For all $j \in [m]$, we attach B leaves to v_j . Let T_j be the set of all leaves incident to v_j for $j \in [m]$, and let $T = \bigcup_{j \in [m]} T_j$. For each integer $e_i \in \mathcal{E}$, we create a vertex u_i and attach $e_i + m$ leaves to it. Let S_i be the set of leaves $\{l_p^i \mid p \leq e_i\}$ for $i \in [n]$, and set $S = \bigcup_{i \in [n]} S_i$. Then, for each $j \in [m]$ and $i \in [n]$, we add the edge $l_{e_i+j}^i v_j$; that is, we connect each v_j with the $(e_i + j)$ -th leaf of the star centered at u_i . This completes the construction of G and the sets of terminals. Notice that deleting $\{v_1, \dots, v_m\}$ leaves a disjoint union of stars, so G has distance to stars at most m .

Now, we claim that the constructed instance $\mathcal{I} = (G, S, T, 1, 2n + m)$ of CHARGING STATION PLACEMENT is a yes-instance if and only if $(\mathcal{E}, m)$ is a yes-instance of UNARY BIN PACKING. First, we observe that a bin packing $\{\mathcal{E}_1, \dots, \mathcal{E}_m\}$ with $\sum_{e \in \mathcal{E}_j} e = B$ yields a feasible charging set $C = \{u_i \mid i \in [n]\} \cup \{v_j \mid j \in [m]\} \cup \{l_{e_i+j}^i \mid e_i \in \mathcal{E}_j\}$ of size $2n + m$, which ensures that each agent starting at a vertex in S_i can reach some T_j . Conversely, we show that any feasible C of size $2n + m$ induces a partition of $\mathcal{E}$ into m multisets, each of total weight B . As $r = 1$, the construction forces any feasible C to include the vertices $\{u_i \mid i \in [n]\} \cup \{v_j \mid j \in [m]\}$, and exactly one vertex from $\{l_{e_i+1}^i, \dots, l_{e_i+m}^i\}$ for each e_i , indicating the bin to which e_i is assigned. Since G has distance to stars at most m , the problem is W[1]-hard parameterized by d_{ts} even when $r = 1$.

By replacing stars with cliques for each connected component of $G - \{v_1, \dots, v_m\}$, we can construct a graph with distance to clusters at most m . The remaining argument is the same as the distance to stars. $\square$

We finally show the W[1]-hardness of CHARGING STATION PLACEMENT parameterized by fvs + c via a reduction from the (k, r) -CENTER problem, defined as follows. Given a graph $G = (V, E)$ and two integers k, r , a set $S \subseteq V$ is called a (k, r) -center if $|S| \leq k$ and the distance from any vertex $v \in V$ to the set S is at most r . The (k, r) -CENTER problem asks whether there exists a (k, r) -center in G . This problem is W[1]-hard when parameterized by fvs + k and admits no algorithm running in time $n^{o(\text{fvs}+k)}$ under the ETH [Katsikarelis *et al.*, 2019].

Theorem 5. CHARGING STATION PLACEMENT is W[1]-hard when parameterized by fvs + c . Furthermore, no algorithm for CHARGING STATION PLACEMENT runs in time $n^{o(\text{fvs}+c)}$ assuming the ETH.

Proof sketch. We give a parameterized reduction from (k, r) -CENTER. Let $(G_0 = (V_0, E_0), k, r)$ be an instance of (k, r) -CENTER, and let $n = |V_0|$. We construct an instance of CHARGING STATION PLACEMENT as follows. First, we create a graph G' starting from G_0 . For each vertex $v \in V_0$, we attach a new pendant vertex, and let S be the set of these n new pendant vertices (i.e., vertices of degree 1). Next, we construct a star-like structure: we introduce a new center vertex p and create $2n$ paths of length $r + 1$, each starting at p . We identify the other endpoints of n of these paths with the

vertices in V_0 one to one. Let T be the set of the n remaining endpoints of the other paths. The resulting graph is G' . Note that $|S| = |T| = n$. This construction ensures that the feedback vertex set number of G' is bounded by a linear function of the feedback vertex set number of the original graph G_0 . Indeed, $\text{fvs}(G') \leq \text{fvs}(G_0) + 1$ holds.

We complete the proof by showing that there exists a (k, r) -center in G_0 if and only if there exists a feasible charger placement for the instance $(G', S, T, r+1, k+1)$ of CHARGING STATION PLACEMENT. $\square$

5 Algorithmic Results

5.1 Parameterized by Terminal Pairs

In this section, we give an FPT algorithm parameterized by $k = |S| = |T|$.

Theorem 6. CHARGING STATION PLACEMENT can be solved in time $k^{O(k)}n^{O(1)}$.

By Proposition 1, it suffices to assume $r = 1$. A set $F = \{H_1, \dots, H_\ell\}$, $\ell \leq k$, of trees in G will be called a *connecting forest*¹ of S and T if there exist partitions $S_1, \dots, S_\ell$ of S and $T_1, \dots, T_\ell$ of T such that, for each $i \in [\ell]$, $|S_i| = |T_i|$, $S_i \cup T_i \subseteq V(H_i)$, and all leaves of H_i belong to $S_i \cup T_i$. Each $H_i \in F$ will be called a *connecting tree*. Let I_i be the set of vertices $u \in V(H_i)$ with $d_{H_i}(u) \geq 2$, i.e., $u \in I_i$ if u is not a leaf of H_i . Also, let $I_F = \bigcup_{i \in [\ell]} I_i$. We show the following key lemma.

Lemma 3. There exists a feasible placement C of size at most c in G if and only if there exists a connecting forest F for S and T with $|I_F| \leq c$.

Based on Lemma 3, we determine whether G has a connecting forest F for S and T with $|I_F| \leq c$. Towards this, we guess partitions $S_1, \dots, S_\ell$ and $T_1, \dots, T_\ell$ of the terminals. For each guessed partition, we can compute a connecting tree H_i of S_i and T_i with the minimum number of inner vertices in time $2^{O(k)}n^{O(1)}$ by reducing it to WEIGHTED STEINER TREE [Lokshtanov and Nederlof, 2010] after guessing the set of inner terminals $X_{\text{in}} \subseteq S_i \cap T_i$ and leaf terminals $X_{\text{out}} = S_i \cap T_i \setminus X_{\text{in}}$. If the sum of inner vertices across all connecting trees is at most c , we conclude that there exists a connecting forest F for S and T with $|I_F| \leq c$ in G . Since the number of guesses is bounded by $k^{O(k)}$, the total running time is $k^{O(k)}n^{O(1)}$, which proves Theorem 6.

5.2 FPT Algorithm by Modular-width

Theorem 7. There exists a $2^{\text{mw}}n^{O(1)}$ -time algorithm for CHARGING STATION PLACEMENT where mw is the modular-width of the input graph.

Let Q be a graph with vertices $q_1, \dots, q_t$, and let $H_1, \dots, H_t$ be t vertex-disjoint graphs. The *substitution* $Q(H_1, \dots, H_t)$ is the graph obtained by replacing each q_i with H_i , and adding all edges between $V(H_i)$ and $V(H_j)$ whenever $\{q_i, q_j\} \in E(Q)$. A *modular decomposition* represents a way to construct G by recursively applying substitutions starting from singletons. The *width* of a modular

decomposition is the maximum number of vertices in any graph Q appearing in the decomposition. The *modular-width* $\text{mw}(G)$ is the minimum width over all decompositions. A modular decomposition of width $\text{mw}(G)$ can be computed in polynomial time [Courmier and Habib, 1994; Tedder *et al.*, 2008; Habib and Paul, 2010]. Since $\text{mw}(G^r) \leq \text{mw}(G)$ for $r \geq 2$ [Hanaka *et al.*, 2024], by Proposition 1, it suffices to solve the case where $r = 1$. Let $G = Q(V_1, \dots, V_t)$ be the top-level decomposition where $t \leq \text{mw}(G)$.

Lemma 4. If $r = 1$ and G is connected, any yes-instance admits a feasible charger placement of size at most c where each module contains at most one charger.

Based on Lemma 4, we guess which modules contain exactly one charger. As $t \leq \text{mw}(G)$, there are at most $2^{\text{mw}(G)}$ guesses. Let $\mathcal{M}' \subseteq \{V_1, \dots, V_t\}$ be a guessed set of modules, and let $Q[\mathcal{M}']$ be the induced subgraph of the quotient graph. For any component in $Q[\mathcal{M}']$ of size at least two, the placement of a charger within each module does not affect inter-module connectivity due to the complete adjacency between connected modules. Thus, we can place a charger on an arbitrary vertex in each such module.

We then consider the placement of a charger for each *isolated* module in $Q[\mathcal{M}']$ (i.e., a module with no neighbors in $\mathcal{M}'$). For an isolated module $M \in \mathcal{M}'$, the placement only affects terminal pairs $\{s, t\} \subseteq M$, as every vertex in M has the same neighbors outside of M . Thus, for each isolated module, we select a vertex $v \in M$ maximizing the number of connected pairs $\{s, t\} \subseteq M$ when a charger is placed on v . Such a vertex $v \in M$ can be found by computing a maximum matching in a bipartite graph constructed based on the connectivity between the vertices in M assuming a charger is placed at v . The running time is dominated by the 2^{mw} guesses, yielding $2^{\text{mw}}n^{O(1)}$.

5.3 FPT Algorithm by Vertex Cover Number

Theorem 7 implies an algorithm with runtime $2^{2^{O(\text{vc})}}n^{O(1)}$. We improve this to single-exponential in vc^2 .

Theorem 8. Given an instance $\mathcal{I}$ of CHARGING STATION PLACEMENT, a minimum charger placement can be computed in time $2^{2^{\text{vc}^2 + \text{vc}}}n^{O(1)}$.

Proof sketch. We first compute a minimum vertex cover $X \subseteq V(G)$ of G in time $2^{\text{vc}}n^{O(1)}$ [Downey and Fellows, 1999]. Then, $I = V(G) \setminus X$ is an independent set of G . We guess at most 2^{vc} possible intersections $X^* = X \cap C$ with a minimum charger placement C . We also guess at most 2^{vc^2} subsets $W \subseteq X \times X$ that represent pairs of vertices in X that are connected by a charger in I .

For a fixed guess (X^*, W) , we construct an instance of SET COVER to find a minimum charger placement in I . Define the universe $U = W$ and $F_v = \{(x, x') \in W \mid x, x' \in N(v)\}$ for each $v \in I$. The set F_v represents the pairs in W that can be connected by a charger on v . Let $\mathcal{F} = \{F_v \mid v \in I\}$. Then $(U, \mathcal{F})$ is an instance of SET COVER introduced in Section 4 corresponding to finding a minimum subset of I in which chargers are placed. Since $|U| \leq \text{vc}^2$, $|\mathcal{F}| \leq n$, and SET COVER can be solved in time

¹Note that F is not necessarily an actual forest as we have no requirement that the trees in F do not share vertices or edges.

$2^{|U|}(|U| + |\mathcal{F}|)^{O(1)}$ [Cygan *et al.*, 2015], we can find an optimal solution $\mathcal{F}' \subseteq \mathcal{F}$ of $(U, \mathcal{F})$ in time $2^{vc^2} n^{O(1)}$. Then we construct a candidate solution $C = X^* \cup \{v \mid F_v \in \mathcal{F}'\}$ and verify whether it is a feasible solution of CHARGING STATION PLACEMENT by Theorem 1. After examining all guesses, we return the smallest solution. Since there are 2^{vc^2+vc} guesses, the total running time is $2^{2vc^2+vc} n^{O(1)}$. $\square$

5.4 Polynomial-Time Algorithm for Trees

In this subsection, we provide a polynomial-time algorithm for trees. In particular, we solve a more general problem called EXT-CHARGING STATION PLACEMENT. In this problem, given an instance $\mathcal{I} = (G, S, T, r, c)$ and a partial solution $P \subseteq V$, the goal is to find a set $C \supseteq P$ such that $|C \setminus P| \leq c$ and C is a feasible solution. Note that, for $P = \emptyset$, the problem is equivalent to CHARGING STATION PLACEMENT.

Theorem 9. EXT-CHARGING STATION PLACEMENT *can be solved in polynomial time when G is a tree.*

To show this, we first root G at an arbitrary vertex w . For any $h \in V$, let G_h be the subtree rooted at h , p_h be the parent of h , and $P_h = P \cap V(G_h)$, $S_h = S \cap V(G_h)$, $T_h = T \cap V(G_h)$. We say that G_h is covered by P if there exist partitions (S_h^1, S_h^2) of S_h and (T_h^1, T_h^2) of T_h such that: (1) $|S_h^1| = |T_h^1|$, (2) there exists a bijection $f : S_h^1 \rightarrow T_h^1$ such that a (P_h, r) -walk between s and $f(s)$ exists in G_h for each $s \in S_h^1$, and (3) for each $x \in S_h^2 \cup T_h^2$, there exists a (P_h, r) -walk W' in $G_h + p_h$ between x and p_h (to be consistent, if $h = w$, we assume a dummy parent p_w for w). For any $h \in V$, we can verify, in polynomial time, whether G_h is covered by P by applying Theorem 1 to an auxiliary graph obtained from G_h by attaching a clique of size $|S_h| + |T_h|$, which consists of $|T_h|$ terminals on S and $|S_h|$ terminals on T , to h . Based on this, we define the following reduction rule.

Reduction Rule: Given an instance (G, S, T, r, c, P) with $c \geq 1$, if there exists $h \in V$ such that G_h is not covered by P , and G_v is covered by P for all $v \in V(G_h) \setminus \{h\}$, create the new instance $(G, S, T, r, c - 1, P \cup \{h\})$.

This rule is safe because such an uncovered G_h forces any feasible solution to add at least one charger in G_h . Moreover, since the subtrees of G_h are covered, placing a charger at h enables all unmatched terminals in G_h to connect via h . We exhaustively apply this reduction rule as long as $c > 0$ and there exists such a vertex h in G .

After thoroughly applying the rule, if $c = 0$, we simply check if P is a feasible solution by using Theorem 1. If $c > 0$, then we can show that $P \cup \{w\}$ is a feasible solution because $G = G_w$ is covered by P . The algorithm runs in polynomial time, as the reduction rule decreases c by 1, and checking whether G_h is covered by P as well as testing the feasibility of P can both be done in polynomial time by Theorem 1.

6 k -Approximation Algorithm

Theorem 10. Let $\mathcal{I} = (G, S, T, r, c)$ be an instance of CHARGING STATION PLACEMENT. Then, a k -approximation solution of $\mathcal{I}$ can be computed in time $O(\sqrt{k}k^4 + k^3n + km)$.

Proof sketch. Let C^* be a minimum charger placement and $f : S \rightarrow T$ be a bijection such that for each $s \in S$, there exists a (C^*, r) -walk between s and $f(s)$. Let $(s^*, f(s^*))$ be a pair maximizing the distance between its terminals i.e., $\text{dist}(s^*, f(s^*)) \geq \text{dist}(s, f(s))$ for all $s \in S$. Since the length of any (C^*, r) -walk between s^* and $f(s^*)$ is at most $\text{dist}(s^*, f(s^*))$, at least $\lceil \frac{\text{dist}(s^*, f(s^*))}{r} \rceil - 1$ vertices must belong to C^* .

Assume that $(s^*, f(s^*))$ is known. We construct a bijection $h : S \rightarrow T$ such that $h(s^*) = f(s^*)$ and $\text{dist}(s, h(s)) \leq \text{dist}(s^*, f(s^*))$ for all $s \in S$ by defining a bipartite graph H where $V(H) = (S \cup T) \setminus \{s^*, f(s^*)\}$, and an edge st is added if and only if $\text{dist}(s, t) \leq \text{dist}(s^*, f(s^*))$. Then a perfect matching in H defines the required bijection h .

We now construct an approximate solution C as follows. For each pair $(s, h(s))$, we take a shortest s - $h(s)$ path and place a charging station on every r -th vertex. Since each path contributes at most $\lceil \text{dist}(s^*, t^*)/r \rceil - 1$ vertices, we have $|C| \leq k(\lceil \text{dist}(s^*, t^*)/r \rceil - 1) \leq k|C^*|$.

Therefore, we compute such a set for each of the $O(k^2)$ possible pairs (s^*, t^*) and take the smallest feasible solution, which is an approximate solution C . $\square$

7 Conclusions

In this work, we consider a natural model of the charging-station placement problem. We present a theoretical study dedicated to the general and parameterized complexity of the problem, picturing the details of the time complexity with respect to both natural and structural parameters.

From a practical perspective, the model is highly pragmatic, yet the existing literature on this topic remains relatively limited. Additionally, the hardness results indicate that, in many cases, alternative approaches are necessary and justify interest in developing heuristics to tackle the problem. Furthermore, our algorithms can be utilized to improve the accuracy of such heuristics.

Additionally, our study gives rise to several theoretical directions, both within the same model and beyond. With respect to parameterized complexity, a particularly interesting question is the parameterization by the combination of the number of charging stations, the distance parameter r , and the maximum degree of the network. The reason is that the closely related (k, r) -CENTER problem becomes FPT under this parameterization, and it would be surprising if this were not the case for CHARGING STATION PLACEMENT.

Further research could explore the relaxation of certain assumptions adopted in this work. The most natural extensions would be to drop the anonymity assumption or to consider restrictions on traveling distance, since these were the main limitations of our model. Most of our results should be easily adaptable to the non-anonymous case; however, this is not true for all of them. For example, Theorem 4 heavily depends on the anonymity assumption. We believe that it would be intriguing to investigate which results can and cannot be generalized depending on the exact models we consider. Moreover, in such comparisons, it is essential to assess how the number of charging stations differs across the considered models.

Acknowledgements

Tesshu Hanaka is partially supported by JSPS KAKENHI Grant Numbers JP22H00513, JP25K03077, and JST, CRONOS, Japan Grant Number JPMJCS24K2.

Nikolaos Melissinos is partially supported by Charles University projects UNCE 24/SCI/008 and PRIMUS 24/SCI/012, and by the project 25-17221S of GAČR.

Hirotaka Ono is partially supported by JSPS KAKENHI Grant Numbers JP22H00513, JP24K02898, JP25K03077, and JST, CRONOS, Japan Grant Number JPMJCS24K2.

References

- [Agarwal *et al.*, 2016] Pankaj K. Agarwal, Jiangwei Pan, and Will Victor. An efficient algorithm for placing electric vehicle charging stations. In Seok-Hee Hong, editor, *27th International Symposium on Algorithms and Computation, ISAAC 2016, Sydney, Australia, December 12-14, 2016*, volume 64 of *LIPICs*, pages 7:1–7:12. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2016.
- [Cesati and Wareham, 1995] Marco Cesati and H Todd Wareham. Parameterized complexity analysis in robot motion planning. In *1995 IEEE International Conference on Systems, Man and Cybernetics. Intelligent Systems for the 21st Century*, volume 1, pages 880–885. IEEE, 1995.
- [Cormen *et al.*, 2009] Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. *Introduction to Algorithms, 3rd Edition*. MIT Press, 2009.
- [Cournier and Habib, 1994] Alain Cournier and Michel Habib. A new linear algorithm for modular decomposition. In Sophie Tison, editor, *Trees in Algebra and Programming - CAAP'94, 19th International Colloquium, Edinburgh, UK, April 11-13, 1994, Proceedings*, volume 787 of *Lecture Notes in Computer Science*, pages 68–84. Springer, 1994.
- [Cygan *et al.*, 2015] Marek Cygan, Fedor V. Fomin, Lukasz Kowalik, Daniel Lokshantov, Dániel Marx, Marcin Pilipczuk, Michal Pilipczuk, and Saket Saurabh. *Parameterized Algorithms*. Springer, 2015.
- [Dantzig and Ramser, 1959] George B Dantzig and John H Ramser. The truck dispatching problem. *Management science*, 6(1):80–91, 1959.
- [Das, 2025] Arun Kumar Das. Charging station placement for limited energy robots. In *Conference on Algorithms and Discrete Applied Mathematics*, pages 97–108. Springer, 2025.
- [David Shepardson, 2025] David Shepardson. 16 U.S. states sue federal government after Trump suspends EV charging programs, December 2025. Accessed: 2025-12-22.
- [Dinur and Steurer, 2014] Irit Dinur and David Steurer. Analytical approach to parallel repetition. In David B. Shmoys, editor, *Symposium on Theory of Computing, STOC 2014, New York, NY, USA, May 31 - June 03, 2014*, pages 624–633. ACM, 2014.
- [Downey and Fellows, 1999] Rodney G. Downey and Michael R. Fellows. *Parameterized Complexity*. Monographs in Computer Science. Springer, 1999.
- [Erickson and LaValle, 2013] Lawrence Erickson and Steven LaValle. A simple, but np-hard, motion planning problem. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 27, pages 1388–1393, 2013.
- [European Automobile Manufacturers' Association, 2024] European Automobile Manufacturers' Association. Electric cars: EU needs 8 times more charging points per year by 2030 to meet CO₂ targets, 2024. Press release, 29 April 2024.
- [Falchetti and Noussan, 2021] Giacomo Falchetti and Michel Noussan. Electric vehicle charging network in Europe: An accessibility and deployment trends analysis. *Transportation Research Part D: Transport and Environment*, 94:102813, 2021.
- [Fioravantes *et al.*, 2025a] Foivos Fioravantes, Dusan Knop, Jan Matyáš Kristan, Nikolaos Melissinos, Michal Opler, and Tung Anh Vu. Solving multiagent path finding on highly centralized networks. In Toby Walsh, Julie Shah, and Zico Kolter, editors, *AAAI-25, Sponsored by the Association for the Advancement of Artificial Intelligence, February 25 - March 4, 2025, Philadelphia, PA, USA*, pages 23186–23193. AAAI Press, 2025.
- [Fioravantes *et al.*, 2025b] Foivos Fioravantes, Dušan Knop, Jan Matyáš Křišť'an, Nikolaos Melissinos, Michal Opler, and Tung Anh Vu. Solving multiagent path finding on highly centralized networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 23186–23193, 2025.
- [Garey and Johnson, 1979] Michael R. Garey and David S. Johnson. *Computers and Intractability: A Guide to the Theory of NP-Completeness*. W. H. Freeman, 1979.
- [Guo *et al.*, 2023] Huihui Guo, Fan Wu, Yunchuan Qin, Ruihui Li, Keqin Li, and Kenli Li. Recent trends in task and motion planning for robotics: A survey. *ACM Computing Surveys*, 55(13s):1–36, 2023.
- [Habib and Paul, 2010] Michel Habib and Christophe Paul. A survey of the algorithmic aspects of modular decomposition. *Comput. Sci. Rev.*, 4(1):41–59, 2010.
- [Hanaka *et al.*, 2024] Tesshu Hanaka, Hirotaka Ono, and Kosuke Sugiyama. Solving distance-constrained labeling problems for small diameter graphs via TSP. *Int. J. Netw. Comput.*, 14(1):26–39, 2024.
- [Jansen *et al.*, 2013] Klaus Jansen, Stefan Kratsch, Dániel Marx, and Ildikó Schlotter. Bin packing with fixed number of bins revisited. *J. Comput. Syst. Sci.*, 79(1):39–49, 2013.
- [Katsikarelis *et al.*, 2019] Ioannis Katsikarelis, Michael Lampis, and Vangelis Th. Paschos. Structural parameters, tight bounds, and approximation for (k, r)-center. *Discret. Appl. Math.*, 264:90–117, 2019.
- [Kumar *et al.*, 2025] Nitesh Kumar, Jaekyung Jackie Lee, Sivakumar Rathinam, Swaroop Darbha, P. B. Sujit, and Rajiv Raman. The persistent robot charging problem for long-duration autonomy. *IEEE Robotics Autom. Lett.*, 10(3):2191–2198, 2025.

- [Kundu and Saha, 2018] Tanmoy Kundu and Indranil Saha. Charging station placement for indoor robotic applications. In *2018 IEEE International Conference on Robotics and Automation, ICRA 2018, Brisbane, Australia, May 21-25, 2018*, pages 3029–3036. IEEE, 2018.
- [Kundu and Saha, 2021] Tanmoy Kundu and Indranil Saha. Mobile recharger path planning and recharge scheduling in a multi-robot environment. In *IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2021, Prague, Czech Republic, September 27 - Oct. 1, 2021*, pages 3635–3642. IEEE, 2021.
- [Kundu and Saha, 2023] Tanmoy Kundu and Indranil Saha. Approximation algorithms for charging station placement for mobile robots. In *IROS*, pages 4770–4776, 2023.
- [Liu *et al.*, 2019] Minghua Liu, Hang Ma, Jiaoyang Li, and Sven Koenig. Task and path planning for multi-agent pickup and delivery. In *Proceedings of the International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS)*, 2019.
- [Lokshtanov and Nederlof, 2010] Daniel Lokshtanov and Jesper Nederlof. Saving space by algebraization. In Leonard J. Schulman, editor, *Proceedings of the 42nd ACM Symposium on Theory of Computing, STOC 2010, Cambridge, Massachusetts, USA, 5-8 June 2010*, pages 321–330. ACM, 2010.
- [Storandt and Funke, 2013] Sabine Storandt and Stefanie Funke. Enabling e-mobility: Facility location for battery loading stations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 27, pages 1341–1347, 2013.
- [Strimel and Veloso, 2014] Grant P Strimel and Manuela M Veloso. Coverage planning with finite resources. In *2014 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 2950–2956. IEEE, 2014.
- [Tedder *et al.*, 2008] Marc Tedder, Derek G. Corneil, Michel Habib, and Christophe Paul. Simpler linear-time modular decomposition via recursive factorizing permutations. In Luca Aceto, Ivan Damgård, Leslie Ann Goldberg, Magnús M. Halldórsson, Anna Ingólfssdóttir, and Igor Walukiewicz, editors, *Automata, Languages and Programming, 35th International Colloquium, ICALP 2008, Reykjavik, Iceland, July 7-11, 2008, Proceedings, Part I: Track A: Algorithms, Automata, Complexity, and Games*, volume 5125 of *Lecture Notes in Computer Science*, pages 634–645. Springer, 2008.
- [Wurman *et al.*, 2008] Peter R Wurman, Raffaello D’Andrea, and Mick Mountz. Coordinating hundreds of cooperative, autonomous vehicles in warehouses. *AI magazine*, 29(1):9–9, 2008.
- [Xiong *et al.*, 2015] Yanhai Xiong, Jiarui Gan, Bo An, Chunyan Miao, and Ana L. C. Bazzan. Optimal electric vehicle charging station placement. In *Proceedings of the Twenty-Fourth International Joint Conference on Artificial Intelligence (IJCAI 2015)*, pages 2662–2668, 2015.
- [Yu and LaValle, 2012] Jingjin Yu and Steven M. LaValle. Multi-agent path planning and network flow. In Emilio Frazzoli, Tomás Lozano-Pérez, Nicholas Roy, and Daniela Rus, editors, *Algorithmic Foundations of Robotics X - Proceedings of the Tenth Workshop on the Algorithmic Foundations of Robotics, WAFR 2012, MIT, Cambridge, Massachusetts, USA, June 13-15 2012*, volume 86 of *Springer Tracts in Advanced Robotics*, pages 157–173. Springer, 2012.
- [Zhang *et al.*, 2022] Weijia Zhang, Hao Liu, Hui Xiong, Tong Xu, Fan Wang, Haoran Xin, and Hua Wu. RLcharge: Imitative multi-agent spatiotemporal reinforcement learning for electric vehicle charging station recommendation. *IEEE Transactions on Knowledge and Data Engineering*, 35(6):6290–6304, 2022.
- [Zhu *et al.*, 2025] Yanchen Zhu, Honghui Zou, Chufan Liu, Yuyu Luo, Yuankai Wu, and Yuxuan Liang. Reinforcement learning for hybrid charging stations planning and operation considering fixed and mobile chargers. In James Kwok, editor, *Proceedings of the Thirty-Fourth International Joint Conference on Artificial Intelligence, IJCAI-25*, pages 10017–10025. International Joint Conferences on Artificial Intelligence Organization, 8 2025. AI and Social Good.